

**Amendments to the Specification:**

Please replace paragraph [0010] with the following amended paragraph:

[0010] For a more detailed description of the embodiments, reference will now be made to the following accompanying drawings:

~~Figure 1 illustrates a wellbore having casing strings and a drill string;~~

~~Figure 2~~ 1 illustrates a flowbore fluid temperature control system; and

~~Figure 3~~ 2 illustrates a flat view of the inside surface of an optional ratchet sleeve in one of the embodiments of the apparatus for changing wellbore fluid temperature.

Please delete the section "DETAILED DESCRIPTION OF THE EMBODIMENTS" and replace the section with the following amended replacement section. Deleted text is shown by strikethrough and the added text is shown by underline.

**DETAILED DESCRIPTION OF THE EMBODIMENTS**

[0011] The drawings and the description below disclose specific embodiments with the understanding that the embodiments are to be considered an exemplification of the principles of the invention, and are not intended to limit the invention to that illustrated and described. Further, it is to be fully recognized that the different teachings of the embodiments discussed below may be employed separately or in any suitable combination to produce desired results.

~~[0012] FIGURE 1 illustrates a wellbore 10 being drilled from a surface 15 and having a drill string 20, a last casing string 25, and a next casing string 30. Wellbore 10 is drilled into a formation 32. Wellbore 10 preferably comprises a cased wellbore section 35 and an open wellbore section 40. The cased wellbore section 35 comprises the portion of wellbore 10 in which the casing strings 25 and 30 have been set. Open wellbore section 40 comprises an uncased section of wellbore 10. The last casing string 25 may comprise a surface casing string. The next casing string 30 may comprise an intermediate casing string. Alternatively, the last casing string 25 and/or the next casing string 30 may also comprise any other suitable casing string. A last casing shoe 45 is preferably disposed at the bottom of last casing string 25. The last casing string 25 may be secured to the formation 32 by a last cement section 50, which is disposed in the annulus between the formation 32 and the last casing string~~

~~25. In alternative embodiments (not illustrated), additional casing strings, such as structural conductor casing strings, and the like, may be disposed in the wellbore 10 between the surface 15 and the last casing string 25. The next casing shoe 55 is preferably disposed at the bottom of the next casing string 30. The next casing string 30 may be secured to the formation 32 by a next cement section 60 disposed in the annulus between the formation 32 and the next casing string 30. The drill string 20 may also comprise a drill bit 65, sub 75, or the like, such as are known in the art. The tubing comprising drill string 20 is likewise well known in the art. The tubing may include coiled tubing, jointed tubing, and any other suitable tubing. The wellbore 10 may also be an off shore or an on shore wellbore.~~

~~[0013] During drilling, drilling fluid is circulated down the flowbore of the drill string 20, through the sub 75 and out the drill bit 65. The drilling fluid can be used to power downhole motors, lubricate the bit, or other downhole functions. The fluid then travels back up the wellbore 10 through the annulus between the wellbore and the drill string 20.~~

~~[0014]~~[0012] The flowbore fluid temperature control system 85 selectively affects the temperature of the fluid flowing through the flowbore of a drill stem by controlling the fluid pressure and flow rate of the flowbore fluid. FIGURES ~~2 and 3~~ 1 and 2 show an embodiment of a flowbore fluid temperature control system 85. FIGURE ~~2~~ 1 illustrates a cross-section view of a portion of the sub 75. As shown, sub 75 comprises a body 77 as well as a flowbore 79, which is a continuation of the flowbore of the drill string ~~20~~. Sub 75 also comprises the flowbore fluid temperature control system 85 that selectively affects the temperature of the fluid flowing through the flowbore 79 as designated by arrow 86. The flowbore fluid temperature control system 85 comprises a valve mechanism 87 that adjusts the fluid flow through the flowbore 79. The valve mechanism 87 as shown in FIGURE ~~2~~ 1 is a multi-position valve mechanism comprising a valve sleeve 91 engaged with the inside of the sub body 77 by threads 93. The outside of the sleeve 91 forms an annulus 93 with the inside of the sub body 77. The valve sleeve 91 also comprises flow ports 95 that allow fluid flow through the sleeve 91 and into the annulus 93 as designated by arrows 97. Within the valve sleeve 91 is a piston 99 that slides to control fluid flow through the flow ports 95. The piston includes seals 101 that prevent fluid flow across the seals 101 between the outside of the piston 99 and the inside of the valve sleeve 91. The piston 99 controls fluid flow through the valve sleeve 91 by selectively opening and closing fluid flow through the flow ports 95 as the piston 99 slides within the valve sleeve 91. The valve sleeve 91 also includes a vent port 103 that

allows the pressure inside of the valve sleeve to adjust with the movement of the piston 99.

~~{0015}~~**[0013]** As best shown in FIGURES ~~2 and 3~~ 1 and 2, the valve sleeve 91 also includes a ratchet sleeve 105. FIGURE ~~3~~ 2 shows the inside of the ratchet sleeve 105 opened flat. As shown, the inside of the ratchet sleeve 105 includes a circumferential groove 107 that reciprocates between first positions 109 and second positions 111 around the inside of the ratchet sleeve 105. The groove 107 also may be incorporated within the valve sleeve 91 itself, without the need for a separate ratchet sleeve 105. As shown in FIGURE ~~3~~ 2, on the outside of the piston 99 is a ratchet lug 113 that travels within the groove 107. As the ratchet lug 113 travels between the first and second positions 109, 111 of the groove 107, the piston 99 reciprocates axially as well as rotates within the valve sleeve 91. At each first and second position 109, 111 the piston 99 selectively opens or closes flow ports 95 to allow varying fluid flow rates through the valve sleeve 91. Also included within the flowbore fluid temperature control system 85 is an optional lock ring 115. The lock ring 115 engages the piston 99 to lock the piston 99 into a selected position, thus maintaining a selected flow rate through the valve sleeve 91.

~~{0016}~~**[0014]** The valve mechanism 87 may also comprise other types of valve mechanisms. For example, the valve sleeve 91 may not include the ratchet sleeve 105 for controlling the position of the piston 99. The valve mechanism 87 may also comprise a single-position valve mechanism such as a poppet valve, an orifice, a reduced-diameter flow path, or a tortuous flow path. The valve mechanism 87 may also comprise single position devices used to create flow restrictions such as a flow restrictor placed in the flowbore. For example, the flow restrictor may be a ball, a sleeve, or bar dropped into the flowbore to create a flow restriction. Altering the restriction in the flowbore may comprise removing the drill string ~~20~~ from the wellbore ~~40~~ to change the restriction of the flowbore. Altering the restriction in the flowbore may also require using wireline fishing methods to install and/or retrieve the restriction device from the flowbore. The flowbore fluid temperature control system 85 may also comprise more than one valve mechanism 87.

~~{0017}~~**[0015]** As shown in FIGURE ~~2~~ 1, the flowbore fluid temperature control system 85 further comprises an actuator mechanism 89, which comprises a spring 117 adapted to compress with the movement of the piston 99. The actuator mechanism 89 may also be comprise any other type of actuator for controlling the valve mechanism 87. For example, the actuator mechanism 89 may comprise a mechanical actuator such as a spring, an electrical actuator such as an electric motor, or a hydraulic actuator such as a hydraulic piston. The actuator mechanism 8 may also be an apparatus that

places the ball, sleeve, bar, or other single position restrictive device into the flowbore.

~~[0018]~~[0016] Not shown is an operating system that selectively operates the actuator mechanism 89 and controls the fluid pressure in the flowbore 79. The operating system of the flowbore fluid temperature control system 85 may comprise a fluid pump located in the drill string-20 or on the surface 45 that controls the fluid pressure within the flowbore 79. The operating system thus operates the actuator mechanism 89, and thus controls the position of the piston 99, by controlling the fluid pressure within the flowbore 79. Increasing the fluid pressure within the flowbore 79 produces a first load on the piston 99 in the direction of the fluid flow 86, thus causing the piston 99 to move and compress the spring 117. As the piston 99 compresses the spring 117, the piston 99 moves axially within the valve sleeve 91 and selectively opens the flow ports 95 to produce a desired flow rate. Moving the piston 99 axially within the valve sleeve 91 also moves the ratchet lug 113 within the ratchet sleeve groove 107. As the piston 99 moves axially to compress the spring 117, the ratchet lug 113 moves to one of the second positions 111, rotating the piston 99 within the valve sleeve 91. Once the ratchet lug 113 reaches one of the selected second positions 111, the piston 99 is prevented from moving further axially to compress the spring 117. Thus, any further increase in fluid pressure within the flowbore 79 will not move the piston 99 to compress the spring 117 any further.

~~[0019]~~[0017] The operating system also selectively decreases the fluid pressure within the flowbore 79. Compressing the spring 117 creates a second load on the piston 99 from the spring 117. A decrease in the fluid pressure within the flowbore 79 allows the spring 117 to expand and thus move the piston 99 in the opposite direction of the fluid flow 86. As the spring 117 moves the piston 99, the piston 99 moves axially within the valve sleeve 91 and selectively closes flow ports 95 to produce a desired flow rate. Moving the piston 99 axially within the valve sleeve 91 also moves the ratchet lug 113 within the ratchet sleeve groove 107. As the spring 117 moves the piston 99 axially, the ratchet lug 113 moves to one of the first positions 109, rotating the piston 99 within the valve sleeve 91. Once the ratchet lug 113 reaches one of the selected first positions 111, the piston 99 is prevented from moving further axially. Thus, any further decrease in fluid pressure within the flowbore 79 will not allow the spring 117 to move the piston 99 any further.

~~[0020]~~[0018] The operating system also moves the piston 99 such that the ratchet lug 113 travels in the ratchet groove 107, reciprocating the piston 99 between the first positions 109 and second positions 111 successively as the piston 99 rotates within the valve sleeve 91. Successive increases and decreases

in the fluid pressure within the flowbore 79 thus cause the piston 99 to selectively move under the force of the fluid pressure and the force of the spring 117 as the ratchet lug 113 travels through the first positions 109 and the second positions 111. The operating system and the actuator mechanism 89 thus control the number of the flow ports 95 that are exposed to the flowpath by selectively positioning the ratchet lug 113, and thus the piston 99 at a desired first position 109 or second position 111. Movement of the ratchet lug 113 within the groove 107, and thus the movement of the piston 99, allows varying fluid flow rates through the valve sleeve 91. When a desired number of exposed flow ports 95 are selected, the operating system may be used to cycle the piston 99 through the positions of the ratchet groove 107 until the piston 99 reaches the position that allows the desired flow rate.

~~{0021}~~{0019} The operating system may remotely operate the actuator mechanism 89 as discussed above. The operating system may also directly operate the actuator mechanism 89. The operating system may also be any system for operating the actuator mechanism 89. For example, the operating system may be mechanical such as a rotation or reciprocation device; hydraulic such as applied pressure, controlled fluid flow rate, or pressure pulse telemetry; electrical such as a generator power supply; or acoustic such as a sonar device.

~~{0022}~~{0020} The flowbore fluid temperature control system 85 operates to control the temperature of the fluid in the flowbore 79. Fluid flows through the flowbore 79 as depicted by direction arrow 86. The fluid then travels through the flow ports 95 of the valve sleeve 91. The fluid then continues to flow through the flowbore 79 as designated by arrows 96 and 98. When the piston 99 is in one the second positions 111, further increasing the flowbore fluid pressure does not move the piston 99 any further axially in the direction of the fluid flow 86. Thus, fluid pressure in the flowbore 86 may be increased without increasing the flow area through the valve sleeve 91. Increasing the fluid pressure in the flowbore 79 above the valve mechanism 87 while maintaining the fluid flow area through the valve mechanism 87 increases the drop in fluid pressure across the valve mechanism 87. Increasing the fluid pressure drop across the valve mechanism 87 increases the temperature of the flowbore 87 fluids as they pass through the valve mechanism 87. The temperature of the flowbore fluid is increased due to the absorption of heat released from the fluid pressure drop. The heat is released as the fluid energy is expended across the fluid pressure drop due to the conservation of energy principle defined by the first law of thermodynamics. The amount of temperature increase of the wellbore fluid is determined by the heat capacity and density of the fluid and the fluid pressure drop. For example, assuming a completely

insulated system where all the heat is absorbed by the fluid, a 1000 lbf/in<sup>2</sup> fluid pressure drop with a fluid that has a heat capacity of 0.5 BTU/lbm-°F and density of 10 lbm/gal, the fluid temperature will increase by 4.9 °F.

~~{0023}~~{0021} While specific embodiments have been shown and described, modifications can be made by one skilled in the art without departing from the spirit or teaching of this invention. The embodiments as described are exemplary only and are not limiting. Many variations and modifications are possible and are within the scope of the invention. Accordingly, the scope of protection is not limited to the embodiments described, but is only limited by the claims that follow, the scope of which shall include all equivalents of the subject matter of the claims.